

U.S. Patent Application Serial No. 10/790,210  
Response to Final OA dated October 18, 2007

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (Previously Presented): An electronic image pickup apparatus comprising:

a main cabinet serving as a handle portion;

a display cabinet having a monitor and attached to the main cabinet as overlapping with the main cabinet;

a lens provided on one of the main cabinet and the display cabinet for picking up an image;

the main cabinet and the display cabinet being pivotal within a plane generally perpendicular to an optical axis of the lens with one end of the main cabinet being connected to one end of the display cabinet; and

a lock device provided between the main cabinet and the display cabinet for holding the display cabinet at a pivot position with respect to the main cabinet, wherein

the optical axis of the lens is aligned with the pivot center axis of the display cabinet,

an image pickup device is located behind the lens, and

the image pickup device is supported so as to be pivotal unitarily with the display cabinet.

Claim 2 (Currently Amended): An electronic image pickup apparatus comprising:

a main cabinet serving as a handle portion;

U.S. Patent Application Serial No. 10/790,210  
Response to Final OA dated October 18, 2007

a display cabinet having a monitor and attached to the main cabinet as overlapping with the main cabinet;

a lens provided on one of the main cabinet and the display cabinet for picking up an image; the main cabinet and the display cabinet being pivotal within a plane generally perpendicular to an optical axis of the lens with one end of the main cabinet being connected to one end of the display cabinet; and

a lock device provided between the main cabinet and the display cabinet for holding the display cabinet at a pivot position with respect to the main cabinet; wherein

the display cabinet includes a proximal portion having a pivot center axis, and a free end portion pivotal with respect to the proximal portion about a pivotal support shaft perpendicular to the pivot center axis, wherein

the main cabinet has a back side surface with image pick-up switches and an opposed front side surface.

the monitor is provided on the free end portion[[:]].

the optical axis of the lens is aligned with the pivot center axis of the display cabinet,

an image pickup device is located behind the lens, and

the optical axis of the lens is crossing to the front side surface of the main cabinet.

Claim 3 (Canceled)

U.S. Patent Application Serial No. 10/790,210  
Response to Final OA dated October 18, 2007

Claim 4 (Original): An electronic image pickup apparatus as set forth in claim 1,  
wherein an operation switch is provided on the main cabinet within reach of a finger of a hand  
holding the main cabinet.

Claim 5 (Original): An electronic image pickup apparatus as set forth in claim 1, wherein  
an operation switch is provided on a proximal portion of the display cabinet.

Claim 6 (Original): An electronic image pickup apparatus as set forth in claim 1, wherein  
a recording star button is provided on a longitudinal end portion of the main cabinet.

Claim 7 (Canceled)

Claim 8 (Previously Presented): An electronic image pickup apparatus as set forth in claim  
1, wherein the image pickup device has a light receiving surface longitudinally aligned with the  
monitor.